

MPX-460P

REMOTE CONTROL FOR VOLUME CONTROL AND ZONE AND SCENE ASSIGNMENT WITH TOUCH SCREEN





Enables volume control, zone assignment, scene assignment, etc.

ESPECIALLY RECOMMENDED IN:



All sectors

DESCRIPTION

The MPX-4088 system is a highly versatile audio matrix, perfect for installations of any size, allowing a multitude of configuration options, DSP signal processing and integrated solutions to common problems such as feedback, covering almost any installation need.



+ Info:

https://fonestar.com/MPX-460P

FONESTAR

Poligono Trascueto. 39600 Revilla de Camargo. Cantabria (España)



MPX-460P is a remote volume control and zone assignment remote control with touch screen for audio matrix mod. MPX-4088.

It connects to the matrix via RJ-45, Cat 5e cable and has an extension link to connect up to 8 MPX-460P in series.

For installations where there are various audio sources and audience areas such as shopping malls, hotels, conference rooms, stadiums, etc.

TECHNICAL CHARACTERISTICS

FEATURES	Remote control for volume control and zone assignment with touch screen for audio matrix mod. MPX-4088. Connection to the matrix via RJ-45 cable, Cat 5e (see note). Link extension for connecting up to 8 MPX-460P in series. Capacitive LCD touch screen. Surface installation. The rear panel is screwed to the wall and the front panel is secured with a screw.
INPUTS	1 RD port for connection to MPX-4088 matrix, RJ-45 (see note)
OUTPUTS	1 extension link, RJ-45
CONTROLS	Volume control, zone and scene allocation
POWER SUPPLY	24 V DC, 100 mA, RD port 24 V DC, 300 mA, euroblock, for connection of more MPX-460P in series.
DIMENSIONS	150 x 115 x 25 mm depth Surface installation.
WEIGHT	0.29 kg
ACCESSORIES	Screws and mounting accessories
NOTE	High quality Cat 5e/6 cables with FTP/SFTP shielding must be used. Cables should have shielded connectors with the cable shielding connected to the connector shield. Maximum cable length 100 m.



+ Info:

https://fonestar.com/MPX-460P