

PUBLIC ADDRESS / POWER AMPLIFIER / SINGLE CHANNEL

FS-11000E

SINGLE CHANNEL POWER STAGE



- ✓ High power: 1.250 W maximum, 1.000 W RMS
- ✓ 4 Ω, line 100 and 70 V speaker output,
- ✓ Protection circuits: Temperature and short circuit

ESPECIALLY RECOMMENDED IN:



All sectors

DESCRIPTION

Power stage 1,250 W maximum, 1,000 W RMS with 4 Ohm loudspeaker output, 100 and 70 V line.

TECHNICAL CHARACTERISTICS



+ Info:
<https://fonestar.com/FS-11000E>

FEATURES	Mono power stage.
POWER	1,250 W maximum, 1,000 W RMS
RESPONSE	30-20,000 Hz \pm 3 dB
DISTORTION	Harmonic: < 1 %
PROTECTION	2 circuits: temperature and short circuit
INPUTS	1 balanced/unbalanced aux line, XLR, euroblock/6.3 mm jack and 2 x RCA 10,000 Ohm, 1.4 V RMS/1 V RMS
OUTPUTS	1 balanced/unbalanced aux line, XLR, euroblock/ 6.3 mm jack and 2 x RCA
FUNCTIONS	Forced ventilation with temperature sensitive speed Protection, signal peak and signal output LED indicators.
CONTROLS	Master volume on rear panel GND lift ground disconnection
IMPEDANCE	4 Ohm and 100 and 70 V lines, screw terminals
POWER SUPPLY	230/115 V AC, 1,400 W maximum
DIMENSIONS	483 x 133 x 440 mm depth. 3 U 19" rack
WEIGHT	21.5 kg



+ Info:
<https://fonestar.com/FS-11000E>