

PUBLIC ADDRESS / POWER AMPLIFIER / SINGLE CHANNEL

# FS-1240E

SINGLE CHANNEL POWER STAGE



- ✓ High power: 300 W maximum, 240 W RMS
- ✓ 4 and 8 Ω, line 100 and 70 V speaker output
- ✓ Protection circuits: Temperature, short circuit and overload

ESPECIALLY RECOMMENDED IN:



All sectors

## DESCRIPTION

Power amplifier 300 W maximum, 240 W RMS with 4 and 8 Ohm loudspeaker output, 100 and 70 V lines.

## TECHNICAL CHARACTERISTICS

FEATURES

Mono power amplifier



+ Info:  
<https://fonestar.com/FS-1240E>

POWER	300 W maximum, 240 W RMS
RESPONSE	50-22,000 Hz $\pm$ 3 dB
DISTORTION	Harmonic: < 0.5%
INPUTS	1 balanced auxiliary line, XLR and 6.3 mm jack 20,000 Ohm, 1 V
OUTPUTS	1 balanced auxiliary line, XLR and 6.3 mm jack
FUNCTIONS	Forced ventilation with variable speed according to the temperature Automatic compression of the input signal LED for protection, signal peak and output signal indicators
PROTECTION	3 circuits: temperature, short circuit and overload
CONTROLS	Tone: bass, mids and trebles $\pm$ 12 dB General volume
IMPEDANCE	4 and 8 Ohm and 100 and 70 V lines, screw terminals and banana plugs
POWER SUPPLY	230/115 V AC, 600 W maximum and 24 V DC, 480 W
DIMENSIONS	483 x 89 x 329 mm depth. 2 U 19" rack
WEIGHT	11.8 kg



+ Info:  
<https://fonestar.com/FS-1240E>