

HIGH POWER / POWER AMPLIFIER / STEREO



STEREO POWER AMPLIFIER





Great power and sound quality.

High performance and stability

It has protection circuits

Very user-friendly and minimal set-up time

ESPECIALLY RECOMMENDED IN:



All sectors

DESCRIPTION

Power amplfier

The SA series amplifiers deliver high power and sound quality with high performance and stability. Operating and power modes: Stereo and parallel: up to 1,500 + 1,500 W RMS@2 Ohm Bridge: up to 1,600 W RMS@8 Ohm

High reliability with: soft start, forced ventilation with variable speed and protection circuits (temperature, short circuit, overload, DC and AC).

Audio inputs with standard connectors: XLR and 6.3 mm jack and volume control for each channel. Speaker outputs with screw terminals and banana plugs or speaker connector.



+ Info: https://fonestar.com/SA-1208

FONESTAR Poligono Trascueto. 39600 Revilla de Camargo. Cantabria (España)



Very user-friendly and minimal set-up time.

Designed for professional use in different mobile events such as discos, concerts, festivals, meetings, etc., as well as for fixed installations in discotheques, pubs, auditoriums, etc.

TECHNICAL CHARACTERISTICS

| FEATURES | Professional stereo power amplifier. |
|----------------|--|
| POWER | Stereo and parallel mode: 1,500 + 1,500 W RMS@2 Ohm 900 + 900 W RMS@4 Ohm 600 + 600 W RMS@8 Ohm Bridge mode: 1,600 W RMS@8 Ohm |
| PROTECTION | Soft start, temperature, short circuit, overload, DC and AC Variable speed forced ventilation |
| CONTROLS | Volume per channel Parallel/stereo/bridge operating mode selector Input limiter and filter GND lift earth disconnection |
| INPUTS | CHA and CH B balanced auxiliary line XLR and jack 6.3 mm, 20,000 Ohm, 0.9 V RMS @ 2 Ohm, 1.1 V RMS @ 4 Ohm, 1.3 V RMS @ 8 Ohm |
| RESPONSE | 10-50,000 Hz, -1.5 dB |
| DISTORTION | Harmonic: <0.03% |
| DAMPING FACTOR | > 500 |
| S/N RATIO | > 103 dB |
| CROSSTALK | > 105 dB |

FONESTAR

+ Info:

https://fonestar.com/SA-1208

Poligono Trascueto. 39600 Revilla de Camargo. Cantabria (España)





| SLEW RATE | 70 V / µs |
|--------------|---|
| OUTPUTS | Speakers: 2-8 Ohm stereo, screw terminals and banana plugs or speaker connector 8 Ohm bridge mono, speaker connector |
| POWER SUPPLY | 230 V AC, 3,000 W maximum |
| DIMENSIONS | 483 x 89 x 480 mm depth 2 U 19" rack |
| WEIGHT | 17.6 kg |



FONESTAR

+ Info:

https://fonestar.com/SA-1208

Poligono Trascueto. 39600 Revilla de Camargo. Cantabria (España)