

HIGH POWER / LOUDSPEAKERS / ACTIVE

ASB-15180U

ACTIVE HIGH-POWER LOUDSPEAKER.



SD



USB

- ✓ Great power and sound quality.
- ✓ USB/SD player with remote control.
- ✓ Woofer protected by front metal grille.
- ✓ Carrying handles, suspension points, legs for floor support and shape of monitor.

ESPECIALLY RECOMMENDED IN:



All sectors



+ Info:

<https://fonestar.com/ASB-15180U>

DESCRIPTION

Fonestar has developed the range of active high-power speakers ASB, the most affordable range of active speakers, which provide great sound quality and integrate all the necessary elements of a professional sound installation.

It has microphone input, line, USB/SD player, mixer, speaker and amplifier. A wide range of playback options and audio inputs make it highly versatile and adaptable.

Class D amplifier with high efficiency and high reliability thanks to low maintenance protection circuits.

Robust injection structure, high transport resistance.

Audio inputs with standard connectors: XLR, jack and RCA.

Powerful, distortion-free sound that provides a precise playback of your music. Passive speaker output with speaker connector.

Remote control is possible thanks to the remote control. Its simple and intuitive use minimizes setup time depending on the installation.

Suspension points and hole in the base for 35 mm tube for suspended or bracket installation, and feet for floor installation. Front metal grille ensures speaker integrity.

Perfect for pubs, gyms, restaurants, small events, children's parties,

TECHNICAL CHARACTERISTICS

FEATURES	<p>Active loudspeaker with extra resistant PP injection box.</p> <p>USB/SD player with remote control..</p> <p>Output for passive loudspeaker.</p> <p>Woofer protected by front metal grille.</p> <p>Carrying handles, suspension points, floor supports and monitor-shaped.</p> <p>Hole in the base for 35 mm tube.</p>
AMPLIFIER	<p>440 W maximum, 220 W RMS Bass: 380 W maximum, 190 W RMS Treble: 60 W maximum, 30 W RMS</p>
PROTECTION	<p>3 protection circuits: short circuit, overload and temperature</p>
LOUDSPEAKERS	<p>1 x 15" woofer: 63.5 mm voice coil and ferrite magnet</p> <p>1 compression driver: 1 ?" diaphragm</p>
RESPONSE	<p>42-18,000 Hz</p>



+ Info:

<https://fonestar.com/ASB-15180U>

INPUTS	3 balanced mics, XLR 1 balanced mic, combo (XLR and 6.3 mm jack) 1 auxiliary line, 2 x RCA
OUTPUTS	1 auxiliary line, 2 x RCA 1 amplified for passive speaker, 8 Ohm speaker connector
INDICATORS	Operation on the front and power and peak on the rear panel
CONTROLS	Input volume and overall volume Input selector: line / MP3 Player control Effects: delay and echo 5-band graphic equalizer
SUSPENSION POINTS	4 points M8
POWER SUPPLY	230/115 V AC, 350 W
DIMENSIONS	460 x 685 x 380 mm depth
WEIGHT	19.05 kg



+ Info:

<https://fonestar.com/ASB-15180U>