

TOWER-40TB

100 V LINE TRANSFORMER SOUND COLUMN.



DESCRIPTION

Sound column with 100V line transformer

These columns are optimized for voice playback and maximum clarity delivery.

Your speaker setup gives you the concentration of sound in your target audience area.

It avoids the coupling production and therefore increases the capacity of amplification of the sound system.

They do not need maintenance to last long, surround and aluminium grid to avoid rusting.

Protection IP-44 for outdoor under cover,

For installations for voice and background music. Especially in enclosures with a lot of reverberation. Such as religious centres, conference rooms, theatres.

TECHNICAL CHARACTERISTICS



Expand product information on:

<https://fonestar.com/es/TOWER-40TB>

FEATURES	Sound column with line transformer
POWER SUPPLY	60 W maximum, 40 W RMS
SPEAKERS	8 x 2 ½" speakers
RESPONSE	170-15,000 Hz
IMPEDANCE	40 W RMS@100 V (250 Ohm) 20 W RMS@100 V (500 Ohm)
SENSIBILITY	93 dB at 1 W/1 m
DISPERSION	155° H x 110° V (1 kHz) 180° H x 70° V (4 kHz)
PROTECTION	IP-44
MATERIAL	Aluminium enclosure Aluminium mesh
COLOUR	White (RAL 9016)
DIMENSIONS	10.6 x 69.5 x 7.5 cm depth
WEIGHT	3.4 kg
ACCESSORIES	Fixing mounts



Expand product information on:
<https://fonestar.com/es/TOWER-40TB>