

PUBLIC ADDRESS / LOUDSPEAKERS / SURFACE

# **SONORA-6N**

LOW IMPEDANCE SURFACE SPEAKER











Crisp, distortion-free sound
Excellent finish and elegant design
IP-66 protection and salt fog
Quick and easy installation



+ Info:

https://fonestar.com/SONORA-6N



ESPECIALLY RECOMMENDED IN:



All sectors

#### **DESCRIPTION**

Low impedance sound system loudspeakers

Based on our extensive experience in the sound sector, FONESTAR has created SONORA.

SONORA is a series of speakers specially designed for PA, musical and background sound applications. Its excellent finish and elegant design allow perfect integration in any space.

They are fully prepared for outdoor use as they feature aluminium grille and protection against water (IP-66) and marine environments.

Besides, SONORA delivers high sound quality with clear, distortion-free sound.

They include all the necessary accessories for easy and quick installation: weatherproofed adjustable fixing mount, stainless steel screws and steel safety cable.

For public address, music and ambient sound applications in public places such as restaurants, cafés, supermarkets, shopping centres, etc.

#### TECHNICAL CHARACTERISTICS

| FEATURES | Low-impedance loudspeaker.  Prepared for outdoor use, with IP-66 protection. |
|----------|--|
| POWER    | 60 W RMS   |
| SPEAKERS | 1 x 6" polypropylene woofer<br>1 x 1" tweeter                                |
| RESPONSE | 75-20,000 Hz   |



+ Info:

https://fonestar.com/SONORA-6N

**FONESTAR** 

Poligono Trascueto. 39600 Revilla de Camargo. Cantabria (España)





| IMPEDANCE                 | 8 Ohm   |
|---------------------------|---|
| SENSITIVITY               | 86 dB @ 1 W/1 m   |
| MAXIMUM ACOUSTIC PRESSURE | 98 dB @ max. W/1 m  |
| COVERAGE ANGLE            | H/V: 150°/150° @500Hz, 150°/120°@1kHz, 100°/50°@2kHz, 175°/175°@4kHz (-6 dB)                                    |
| PROTECTIONS               | IP-66 according to EN 60529 IEC 60068-2-11 Enviromental Test (Salt mist)  |
| MATERIAL                  | ABS Aluminium mesh grille Mount with weatherproof treatment Stainless steel screws                              |
| CONNECTORS                | Euroblock in and out for cable 0.25 – 2.5 mm² cross section   |
| TMEPERATURE RANGE         | -10°C to 60°C   |
| COLOUR                    | Black (RAL 9005)  |
| DIMENSIONS                | Loudspeaker: 199 x 322 x 181 mm depth<br>Mount wall plate: 102 x 165 mm<br>Loudspeaker with mount: 284 mm depth |
| WEIGHT                    | 2.4 kg  |
| ACCESSORIES               | Adjustable mounting bracket ± 60° in all directions.  Steel safety cable  |





+ Info:

https://fonestar.com/SONORA-6N










**FONESTAR** 

escription


Units Scale mm 1:4

## **FONESTAR**

## ■ Impedance vs Frequency



## SPL vs Frequency





+ Info https://fonestar.com/SONORA-6N


**FONESTAR** 

Polígono Trascueto. 39600 Revilla de Camargo. Cantabria (España)

## **FONESTAR**



### SPL vs Angle





+ Info

https://fonestar.com/SONORA-6N