

PUBLIC ADDRESS / AMPLIFIERS / STEREO

WA-2151RC

COMPACT STEREO AMPLIFIER







Great reliability and sound quality.



Compact size



For surface mounting



Easily hidden

ESPECIALLY RECOMMENDED IN:



All sectors

DESCRIPTION

Class D stereo amplifier, 2 x 15 W RMS with remote control.

Compact and robust construction. Remote control for power and volume.

Volume control with motorized potentiometer. Highly efficient class D amplification circuit.

Specially designed for audio installations which require high reliability and quality sound.

TECHNICAL CHARACTERISTICS



+ Info:

https://fonestar.com/WA-2151RC

FONESTAR

Poligono Trascueto. 39600 Revilla de Camargo. Cantabria (España)



FEATURES	Class D stereo amplifier. Steel box for surface assembly. Remote control. Volume control with motorized potentiometer. Stereo loudspeaker output.
POWER	2 x 15 W RMS at 4 Ohm
PROTECTION	Short circuit and temperature
RESPONSE	20-20,000 Hz
DISTORTION	Harmonic: 0.06% at 1 kHz
INPUTS	1 aux line, 2 x RCA
OUTPUTS	4-8 Ohm loudspeakers, euroblock
CONTROLS	Standby and general volume
INDICATORS	LED power, standby, volume level, mute and IR indicator
POWER SUPPLY	12 V DC, 2 A with adapter included
DIMENSIONS	145 x 41 x 97 mm depth
WEIGHT	0.5 kg (with adapter included)
ACCESSORIES	Extension cable with remote control



+ Info:

https://fonestar.com/WA-2151RC