

MICROPHONES / SIMULTANEOUS INTERPRETATION SYSTEM / SIMULTANEOUS INTERPRETATION SYSTEM

# SCT-600

SIMULTANEOUS INTERPRETATION TRANSMITTER



ESPECIALLY RECOMMENDED IN:



Education



Offices

## DESCRIPTION

Simultaneous interpretation system for up to 5 languages with transmission via IR radiators. Allows connection of up to 6 translation desks. High sound quality without interference with lighting systems.

## TECHNICAL CHARACTERISTICS

FEATURES	SCT simultaneous interpretation system transmitter. Up to 5 languages besides the original language. Up to 10 SCT-61M or SCT-122M microphones can be connected in cascade. Automatic control of output volume.
RESPONSE	100-14,000 Hz



+ Info:  
<https://fonestar.com/SCT-600>

INDICATORS	Output level in each channel
INPUTS	6 lines, RCA 18,000 Ohm 2 V
OUTPUTS	6 lines, RCA 600 Ohm 1 V 2 radiators, BNC 50 Ohm 2 interpretation units, DB25
S/N RATIO	>75 dB
POWER SUPPLY	110-240 V AC, 40 W
DIMENSIONS	483 x 89 x 355 mm depth
WEIGHT	7 kg
ACCESSORIES	10 m interconnection cable for interpretation units, DB25 2 x audio cables, 6.3 mm mono jack to RCA



+ Info:  
<https://fonestar.com/SCT-600>