

PUBLIC ADDRESS / LOUDSPEAKERS / CEILING

GAT-1SUB

100 V LINE TRANSFORMER CEILING SUBWOOFER SPEAKER



- ✓ Great bass response
- ✓ BASS REFLEX boost
- ✓ Anchorage installation system

ESPECIALLY RECOMMENDED IN:



All sectors



+ Info:

<https://fonestar.com/GAT-1SUB>

DESCRIPTION

Subwoofer ceiling loudspeaker with round grille and fire-resistant steel case. Bass reflex radiation system for bass reinforcement in 100 V line installations.

TECHNICAL CHARACTERISTICS

FEATURES	Subwoofer ceiling loudspeaker with 100 V line transformer and low impedance, round grille and fireproof case. Bass reflex radiation system. Bass reinforcement in 100 V line installations.
POWER	90 W maximum, 60 W RMS
LOUDSPEAKERS	1 x 8" woofer
RESPONSE	40-170 Hz
IMPEDANCE	High Z 100 V line: 166 Ohm (60 W), 333 Ohm (30 W), 666 Ohm (15 W) Low Z: 8 Ohm
SENSITIVITY	86 dB at 1 W/1 m
SUSPENSION POINTS	4 points for hanging from the ceiling
MATERIAL	ABS, steel grille and fireproof case. Ceramic connectors
COLOUR	White
DIMENSIONS	350 mm Ø x 320 mm depth
HOLE	309 mm Ø



+ Info:
<https://fonestar.com/GAT-1SUB>

WEIGHT	7.5 kg
ACCESSORIES	Chain for hanging
	Installation system with catches Fixing system



+ Info:

<https://fonestar.com/GAT-1SUB>