

PUBLIC ADDRESS / LOUDSPEAKERS / SOUND PROJECTORS

PF-25TD

BIDIRECTIONAL SOUND PROJECTOR



- ✓ Excellent sound quality
- ✓ Bidirectional sound
- ✓ Excellent finish and elegant design
- ✓ IP-55 protection

ESPECIALLY RECOMMENDED IN:



All sectors



+ Info:
<https://fonestar.com/PF-25TD>

DESCRIPTION

Bidirectional sound projector with 100 V line transformer suitable for public address installations with excellent vocal and musical response. IP-55 protection for outdoor installation.

High impedance sound projector

Sound projector with great features, design and manufacture.

Its features make it very suitable for indoor or outdoor PA installations, IP-55 protection.

ABS built with sealed housing, ensuring its integrity and operation in harsh environments.

It delivers crisp, clean sound, perfect for both public address applications and background music.

With a coverage angle of 170° and a sensitivity of 91 dB at 1 W/1 m, they can reach large distances and cover large areas.

For public address and background music applications in 100 V line installations in shopping centres, schools, hospitals, sports facilities, industrial buildings, etc.

TECHNICAL CHARACTERISTICS

FEATURES	Bidirectional sound projector with 100 V line transformer.
POWER	15 W maximum, 10 W RMS
LOUDSPEAKERS	2 x 5" double cone, varnished cardboard
RESPONSE	130-15,000 Hz
IMPEDANCE	10 W RMS@100V (1,000 Ohm) 5 W RMS@100V (2,000 Ohm) 2.5 W RMS@100V (4,000 Ohm)
SENSITIVITY	91 dB at 1 W/1 m
DISPERSION	Bidirectional 170°@1kHz, 100°@2kHz, 60°@4kHz (-6dB)



+ Info:
<https://fonestar.com/PF-25TD>

PROTECTION	IP55 in compliance with 60529
MATERIAL	ABS. Hermetic casing Aluminium mount and grille Stainless steel screws
TEMPERATURE RANGE	-25? ~ 55?
COLOUR	White (RAL 9016)
DIMENSIONS	138 mm Ø x 200 mm depth
WEIGHT	1.7 kg
ACCESSORIES	Adjustable fixing mount



+ Info:
<https://fonestar.com/PF-25TD>