

HIGH POWER / POWER AMPLIFIER / STEREO

SA2-3400

STEREO POWER AMPLIFIER





Great power and sound quality.



High performance and stability



It has protection circuits



Very user-friendly and minimal set-up time

ESPECIALLY RECOMMENDED IN:



All sectors

DESCRIPTION

Professional stereo power amplifier

The SA2 series amplifiers deliver high power and sound quality with high performance and stability.

Operating and power modes:

Stereo and parallel up to 1,700 + 1,700 W RMS@2 Ohm

Bridge mode up to 3.400 W RMS@4 Ohm

High reliability with soft start, temperature protection, short circuit, overload, clip limiter, continuous voltage, ultrasound and RF.

Incorporates 2 variable speed fans.



+ Info:

https://fonestar.com/SA2-3400

FONESTAR

Poligono Trascueto. 39600 Revilla de Camargo. Cantabria (España)



Audio inputs with XLR connection and volume control of each channel. Speaker outputs with speaker connector.

Very user-friendly and minimal set-up time.

Designed for professional use in different mobile events such as discos, concerts, festivals, meetings, etc., as well as for fixed installations in discotheques, pubs, auditoriums, etc.

TECHNICAL CHARACTERISTICS

FEATURES	Professional stereo power amplifier.
POWER	Stereo and parallel mode: 850 + 850 W RMS@8 Ohm 1,275 + 1,275 W RMS@4 Ohm 1,700 + 1,700 W RMS@2 Ohm Bridge mode: 2,550 W RMS@8 Ohm 3,400 W RMS@4 Ohm
PROTECTION	Soft start, temperature, short circuit, overload, clip limiter, direct voltage, ultrasound and RF 2 variable speed fans
CONTROLS	Volume per channel Stereo/parallel/bridge operating mode selector Sensitivity selector GND lift earth disconnection 30Hz high pass filter
INPUTS	2 balanced XLR auxiliary line inputs
RESPONSE	20-20,000 Hz
DISTORTION	Harmonic: <0.08%
DAMPING FACTOR	400



+ Info:

https://fonestar.com/SA2-3400



S/N RATIO	> 95 dB
OUTPUTS	2 speaker outputs
POWER SUPPLY	230 V AC, 1,880 W maximum
DIMENSIONS	483 x 89 x 488 mm depth. 2 U 19" rack
WEIGHT	23 kg



+ Info:

https://fonestar.com/SA2-3400