

PUBLIC ADDRESS / LOUDSPEAKERS / SURFACE

AMBIENT-BT20A

ACTIVE AND PASSIVE SURFACE SPEAKER PAIR.







Great power and sound quality.



Compact size



High efficiency class-D amplifier



Includes fixing bracket with swivelling arm and steel safety wire

ESPECIALLY RECOMMENDED IN:



All sectors



+ Info:

https://fonestar.com/AMBIENT-BT20A



DESCRIPTION

Pair of autoamplified speakers from the AMBIENT series with great sound quality. Recommended for installations in public premises such as restaurants, cafés, supermarkets, shopping centres, etc.

Excellent finish, high powered and resistant, in a compact size.

Pair composed of one active loudspeaker with amplification circuit and output for the connection of the other passive loudspeaker.

The loudspeakers include a wall mount with adjustable arm and steel safety cable allowing easy installation and positioning.

TECHNICAL CHARACTERISTICS

FEATURES	Pair of autoamplified speakers Composed of one active loudspeaker with amplifier and another passive loudspeaker. Highly efficient class-D amplifier. Shielded magnet loudspeaker. Bass reflex reinforcement system.
POWER	2 x 10 W RMS Class-D amplifier Protection circuit
LOUDSPEAKERS	1 x 3" polypropylene woofer, 20.4 mm coil with shielded magnet
RESPONSE	150 - 20,000 Hz
INPUTS	1 aux line, 2 x RCA 775 mV
OUTPUTS	Loudspeaker: 6.3 mm jack
INDICATORS	LED operating lights
CONTROLS	On/off and volume
COLOUR	Black (RAL 9017)



+ Info:

https://fonestar.com/AMBIENT-BT20A



MATERIAL	Steel grille and ABS casing
POWER SUPPLY	230 V AC, 60 W
DIMENSIONS	115 x 175 x 107 mm depth
WEIGHT	Active loudspeaker: 1.3 kg Passive loudspeaker: 0.8 kg
ACCESSORIES	Fixing mounts with adjustable arm and steel safety cable 3 m loudspeaker cable



+ Info:

https://fonestar.com/AMBIENT-BT20A