

MIX-12PRO

STUDIO MIXER.



DESCRIPTION

Professional 12-channel stereo mixer with PC audio card and Bluetooth®/USB recorder/player.

Connect the mixer to your PC as an audio card. You can play audio content from your PC and record audio on your PC simultaneously.

Bluetooth/USB recorder and player, play music or record the event without PC.

Includes 24-bit digital effects processor (16 effects), which will give an extra touch of quality to your events. It also has 48 V phantom power for the use of condenser microphones.

Ideal for use at all kinds of events, press rooms, live performances, concerts, etc.

TECHNICAL CHARACTERISTICS



Expand product information on: https://fonestar.com/es/MIX-12PRO

FONESTAR

Poligono Trascueto. 39600 Revilla de Camargo. Cantabria (España)



FEATURES	Professional 12-channel mixer with 2 outputs and independent volume controls. USB audio input/output for PC connection as an audio card, allows simultaneous PC audio playback and recording. Bluetooth receiver. USB recorder/player. 16 digital effects processor.
USB PLAYER	Playback formats: WAV and MP3 MP3 recording USB port for connection of USB drives or connection to PC as audio card Supports memory up to 128 GB
INPUTS	12 balanced XLR mics, 600 Ohm 2 mV (LED peak, 1 kHz, 20 mV RMS) 12 unbalanced lines 6.3 mm jack, 47.000 Ohm 45 mV (LED peak, 1 kHz, 180 mV RMS) 2 balanced returns, 2 x 6'3 mm jack, 47.000 Ohm 300 mV RMS 1 USB/PC, stereo
CONTROLS	Mic/line: bass suppressionfilter (18 dB/octave, 75 Hz), gain, bass (±15 dB, 80 Hz), mid (±15 dB, 2,500 Hz), treble (±15 dB, 12,000 Hz), aux/EFX send, pan, mute and slide volume control USB recorder/player: mode, play/pause/rec, fast forward and rewind, bass (±15 dB, 80 Hz), treble (±15 dB, 12,000 Hz) and slider volume control Main: sliding volume control Phones: volume control Post-fader aux send: volume control Aux return: volume control DSP effects processor: effect selection, repeat and slider volume control
FUNCTIONS	Sliders per channel 3-band EQ on channels 1 to 12 2-band equaliser on USB recorder/player Overload and master output level indicator lights
OUTPUTS	1 stereo main (2 x XLR or 2 x 6.3 mm jack), 5 V RMS 1 stereo line, 2 x RCA, 5 V RMS 1 post-fader send, 6'3 mm jack, 5 V RMS 1 stereo headphones, 6.3 mm jack 1 USB/PC, stereo
PHANTOM	48 V, selectable
RESPONSE	20-20,000 Hz
DISTORTION	Harmonic: 0.07 %



Expand product information on: https://fonestar.com/es/MIX-12PRO

FONESTAR

Poligono Trascueto. 39600 Revilla de Camargo. Cantabria (España)



S/N RATIO	> 65 dB
POWER SUPPLY	100-240 V AC, 20 W maximum
DIMENSIONS	500 x 85 x 320 mm depth
WEIGHT	4.7 kg



Expand product information on: https://fonestar.com/es/MIX-12PRO