

AIP-IO-12R

DESC. CORTA



DESCRIPTION

AIP-IO series allows programmable isolated inputs for contact closure event activation and output relays for external device control and third-wire control.

You can choose the combination that best suits your installation, in groups of 4, with up to 16 inputs or relays per device.

AIP-IO-12R has 12 programmable general purpose outputs for external device control and third-wire control.

AIP ecosystem is a 100% scalable solution, with no limit to the number of AIP devices and channels, auto-discovery service when connected to the network and intuitive configuration and control software (AIP-Go).

For professional installations in large shopping centres, schools, office buildings, etc.

TECHNICAL CHARACTERISTICS

| | |
|----------|--|
| FEATURES | General purpose 12-output device for IP audio system. Remote update via PC software or locally via USB. |
| INPUTS | 1 ethernet 10/100 Base T, RJ-45 USB port for software update |
| OUTPUTS | 12 output relays for external device control and third-wire control, euroblock |



Expand product information on:
<https://fonestar.com/es/AIP-IO-12R>

| | |
|--------------|---|
| POWER SUPPLY | 100-240 V AC, 10 W |
| DIMENSIONS | 435 x 45 x 197 mm depth. 1 U 19" rack |
| WEIGHT | 1.6 kg |
| ACCESSORIES | 19" rack mount brackets |
| SOFTWARE | PC software with automatic detection of AIP series devices connected in the LAN network Remote adjustment of configuration parameters Firmware update |



Expand product information on:
<https://fonestar.com/es/AIP-IO-12R>