

# AIP-IO-12S4R

DESC. CORTA



## DESCRIPTION

AIP-IO series allows programmable isolated inputs for contact closure event activation and output relays for external device control and third-wire control.

You can choose the combination that best suits your installation, in groups of 4, with up to 16 inputs or relays per device.

AIP-IO-12S4R has 12 programmable isolated inputs for contact closure event activation and 4 programmable general purpose outputs for external device control and third-wire control.

AIP ecosystem is a 100% scalable solution, with no limit to the number of AIP devices and channels, auto-discovery service when connected to the network and intuitive configuration and control software (AIP-Go).

For professional installations in large shopping centres, schools, office buildings, etc.

## TECHNICAL CHARACTERISTICS

|          |   |
|----------|---|
| FEATURES | Isolated 12-input and 4-output general purpose device for IP audio system. Remote update via PC software or locally via USB.                      |
| INPUTS   | 1 ethernet 10/100 Base T, RJ-45<br>12 isolated programmable input for contact closure event activation, euroblock<br>USB port for software update |



Expand product information on:  
<https://fonestar.com/es/AIP-IO-12S4R>

|              |   |
|--------------|---|
| OUTPUTS      | 4 output relays for external device control and third-wire control, euroblock   |
| POWER SUPPLY | 100-240 V AC, 10 W  |
| DIMENSIONS   | 435 x 45 x 197 mm depth. 1 U 19" rack   |
| WEIGHT       | 1.6 kg  |
| ACCESSORIES  | 19" rack mount brackets   |
| SOFTWARE     | PC software with automatic detection of AIP series devices connected in the LAN network<br>Remote adjustment of configuration parameters<br>Firmware update |



Expand product information on:  
<https://fonestar.com/es/AIP-IO-12S4R>