## **AIP-10-8S**

ISOLATED 8-INPUT DEVICE FOR IP AUDIO SYSTEM



## **DESCRIPTION**

AIP-IO series allows programmable isolated inputs for contact closure event activation and output relays for external device control and third-wire control.

You can choose the combination that best suits your installation, in groups of 4, with up to 16 inputs or relays per device.

AIP-IO-8S has 8 programmable isolated inputs for contact closure event activation.

AIP ecosystem is a 100% scalable solution, with no limit to the number of AIP devices and channels, autodiscovery service when connected to the network and intuitive configuration and control software (AIP-Go).

For professional installations in large shopping centres, schools, office buildings, etc.

## **TECHNICAL CHARACTERISTICS**

| FEATUR | ES |
|--------|----|
|        |    |

8 isolated input device for IP audio system. Remote update via PC software or locally via USB.

1 ethernet 10/100 Base T, RJ-45

INPUTS

8 isolated programmable input for contact closure event activation, euroblock USB port for software update



Expand product information on: https://fonestar.com/es/AIP-IO-8S

**FONESTAR** 

Poligono Trascueto. 39600 Revilla de Camargo. Cantabria (España)



| POWER SUPPLY | 100-240 V AC, 10 W  |
|--------------|---|
| DIMENSIONS   | 435x 45 x 197 mm depth. 1 U 19" rack  |
| WEIGHT       | 1.6 kg  |
| ACCESSORIES  | 19" rack mount brackets   |
| SOFTWARE     | PC software with automatic detection of AIP series devices connected in the LAN network Remote adjustment of configuration parameters Firmware update |



Expand product information on: https://fonestar.com/es/AIP-IO-8S