

# AIP-IO-8S8R

DESC. CORTA



## DESCRIPTION

AIP-IO series allows programmable isolated inputs for contact closure event activation and output relays for external device control and third-wire control.

You can choose the combination that best suits your installation, in groups of 4, with up to 16 inputs or relays per device.

AIP-IO-8S8R has 8 programmable isolated inputs for contact closure event activation and 8 programmable general purpose outputs for external device control and third-wire control.

AIP ecosystem is a 100% scalable solution, with no limit to the number of AIP devices and channels, auto-discovery service when connected to the network and intuitive configuration and control software (AIP-Go).

For professional installations in large shopping centres, schools, office buildings, etc.

## TECHNICAL CHARACTERISTICS

FEATURES	Isolated 8-input and 8-output general purpose device for IP audio system. Remote update via PC software or locally via USB.
INPUTS	1 ethernet 10/100 Base T, RJ-45 8 isolated programmable input for contact closure event activation, euroblock USB port for software update



Expand product information on:  
<https://fonestar.com/es/AIP-IO-8S8R>

OUTPUTS	8 output relays for external device control and third-wire control, euroblock
POWER SUPPLY	100-240 V AC, 10 W
DIMENSIONS	435 x 45 x 197 mm depth. 1 U 19" rack
WEIGHT	1.6 kg
ACCESSORIES	19" rack mount brackets
SOFTWARE	PC software with automatic detection of AIP series devices connected in the LAN network Remote adjustment of configuration parameters Firmware update



Expand product information on:  
<https://fonestar.com/es/AIP-IO-8S8R>