

# AQUA-8TG

100 V LINE TRANSFORMER CEILING SPEAKER



## DESCRIPTION

Loudspeaker with 100 V line transformer and low impedance.

Based on our extensive experience in the sound sector, FONESTAR has created AQUA.

AQUA is a series of loudspeakers specially designed for public address and ambient sound applications in large outdoor spaces.

Its robust and compact construction, excellent finish and elegant design, allow for a perfect blend into any space.

They are fully prepared for outdoor use as they are equipped with a weatherproofed grille and an adjustable fixing mount, stainless steel screws and water protection (IP-66).

In addition, AQUA has a high-powered 8" woofer and diffuser motor that delivers a rich, defined and distortion-free sound. Enhanced bass response. Provides powerful sound and wide coverage.

Includes all necessary accessories for a quick and easy installation: adjustable fixing mount, screws and steel safety cable.



Expand product information on:  
<https://fonestar.com/es/AQUA-8TG>

Perfect for public address and ambient sound applications in outdoor areas such as stadiums, theme parks, cultural activities, shopping centres, etc.

**TECHNICAL CHARACTERISTICS**

FEATURES	<p>Loudspeaker with 100 V line transformer and low impedance 8 Ohm.                  High-powered woofer and diffuser motor for a richly nuanced, defined and distortion-free sound.                  Sound with great range and coverage. Enhanced bass.                  Robust, compact construction.                  Weatherproofed grille.                  Outdoor-ready, IP-66 water protection and anti-corrosion materials.</p>
POWER	<p>250 W max, 200 W RMS</p>
LOUDSPEAKERS	<p>1 x 8" woofer                  1 x 1" compression motor</p>
RESPONSE	<p>70-20.000 Hz (-10 dB)</p>
IMPEDANCE	<p>200 W RMS@8 Ohm                  200 W RMS@100 V/70 V (50 Ohm/25 Ohm)                  100 W RMS@70 V (50 Ohm)                  150 W RMS@100 V (66 Ohm)                  75 W RMS@100 V/70 V (133 Ohm/66 Ohm)                  37.5 W RMS@70 V (133 Ohm)</p>
SENSITIVITY	<p>96 dB at 1 W/1 m</p>
SOUND PRESSURE	<p>119 dB max power at 1 m</p>
COVERAGE ANGLE	<p>80° H x 50° V at 1 kHz/-6 dB</p>
CROSSOVER	<p>2 ways                  Crossover frequency at 3.000 Hz</p>
SWITCH	<p>W selector at high Z and low Z</p>



Expand product information on:  
<https://fonestar.com/es/AQUA-8TG>

PROTECTION	IP-66
MATERIAL	Weatherproofed steel grille and mount Stainless steel screws
CONNECTORS	Screw terminals
TEMPERATURE RANGE	TEMPERATURE RANGE
COLOUR	Grey (RAL 7035)
DIMENSIONS	319 x 308 x 350 mm depth
WEIGHT	12.2 kg
ACCESSORIES	Adjustable fixing mount Steel safety cable



Expand product information on:  
<https://fonestar.com/es/AQUA-8TG>