



WIRELESS HDMI EXTENDER



DESCRIPTION

Wireless HDMI extension

This kit, consisting of transmitter and receiver, allows the transmission of an HDMI signal wirelessly up to 100 m distance in direct vision for a resolution of up to 1080p@60 Hz. It uses the 5.8 GHz band to transmit an HDMI signal with H.265 compression, as well as transmitting the IR signal from the remote control for remote control of the source.

It is a perfect alternative to using HDMI cabling, making it perfect for installations where cabling is not possible. In addition, installation time is greatly reduced, thanks to plug & play installation with no configuration required.

It has a latency of less than 120ms for virtually lag-free video and audio transmission.

It is perfect for commercial applications, advertising, healthcare, education, conference rooms, audio-visual events, trade fairs, home use, etc.



Expand product information on: https://fonestar.com/es/VS-2490HD

FONESTAR Poligono Trascueto. 39600 Revilla de Camargo. Cantabria (España)



TECHNICAL CHARACTERISTICS

FEATURES	Wireless HDMI extension with H.265 compression technology. Consisting of 1 transmitter and 1 receiver. Transmission distance up to 100 m in direct vision for 1080p@60 Hz resolution. Transmission frequency 5.8 GHz. Compatible with 1080p@60 Hz. Easy installation with no configuration required. No interference with Wi-Fi networks. No need for direct line-of-sight between devices (maximum transmission distance is reduced). Remote control extender.
HDMI	1.3
HDCP	1.4
LATENCY	<120 ms
POWER SUPPLY	Transmitter and receiver: 5 V DC, 2 A with adapters included
DIMENSIONS	Transmitter and receiver: 76 x 23 x 103 mm depth
WEIGHT	2 x 0.12 kg
ACCESSORIES	1 remote control IR transmitter cable, 1.5 m 1 remote control IR receiver cable, 1.5 m

FONESTAR

Expand product information on: https://fonestar.com/es/VS-2490HD

Poligono Trascueto. 39600 Revilla de Camargo. Cantabria (España)