

SISTEMAS Y CONTROL / SISTEMAS DE ZONAS / DIGITAL

# NMX-WP

REMOTE CONTROL UNIT FOR NMX SERIES MATRICES



ETHERNET



FULL IP


 SCALABLE  
INSTALLATIONS

 CUSTOMISED  
CONFIGURATION


UDP



PoE

- ✓ Up to 32 programmable menus.
- ✓ Simple connection via Ethernet and POE power.

ESPECIALLY RECOMMENDED IN:



Sports facilities



Hotels



All sectors



+ Info:

<https://fonestar.com/NMX-WP>

## DESCRIPTION

Programmable remote control. Remote control for the NMX series matrices. The user will be able to interact with the sound system locally, without the need to access the complex matrix configuration. It allows the controller to be configured with the most common functions and simplifies system management for the end user. It has a neutral design with a selection button and information display that allows the user to interact easily. The control knob allows the menus to be programmed to adapt them to the user's needs. It is programmable and customisable with PC control software. You can select functions such as volume control, gain control, mute, scene recall and special actions with UDP, RS-232 or RS-485 commands. Multiple control remotes can be used in one installation. Easy connection via Ethernet and POE power. Controller for applications where volume control and source selection is required locally in the zones, as well as other types of actions. Such as music bars, restaurants, hotels, shopping centres, conference rooms, etc.

## TECHNICAL CHARACTERISTICS

INPUTS	1 x LAN port for local area network connection, RJ-45
FEATURES	Programmable remote control. Neutral design with a selection button and information display. Up to 32 programmable menus. Programmable and customisable with PC control software. The main functions are volume control, gain control, Mute, scene call and UDP, RS-232 or RS-485 commands. Supports multiple controllers in one installation. Simple connection via Ethernet and POE power. Installation in 86 x 86 mm standard box.
CONTROLS	Selection and confirmation button UDP control protocol
POWER SUPPLY	POE, consumption <300 mA
DIMENSIONS	Totals: 86 x 86 x 50 mm depth Inset: 57 x 62 x 30 mm depth Distance between screws: 60 mm
WEIGHT	0.25 kg
OPTIONAL	DOT-BOX-B: Surface mounting box



+ Info:  
<https://fonestar.com/NMX-WP>

