

MICROPHONES / SIMULTANEOUS INTERPRETATION SYSTEM / SIMULTANEOUS INTERPRETATION SYSTEM

IR-600T

IR RADIATOR FOR SIMULTANEOUS INTERPRETING SYSTEM



ESPECIALLY RECOMMENDED IN:



Education



Offices



+ Info:

<https://fonestar.com/IR-600T>

DESCRIPTION

IR radiator for interpretation system. Wide coverage, extendable with cascade connection.

TECHNICAL CHARACTERISTICS

FEATURES	IR radiator for SCT simultaneous translation system. Covered area of up to 600 m ² per radiator.
INPUTS	Signal In, BNC, for connection with the transmitter Recommended 50 Ohm shielded coaxial cable, RG-58. Maximum length of a single cable is 100 m. If there are more cables with more receivers, the total length must not exceed 200 m.
OUTPUTS	Signal Out, BNC, for cascading with other IR-600T radiators
OUTPUT POWER	25 W
RANGE	Up to 30 m
DISPERSION	135°
POWER SUPPLY	110-240 V AC, 55 W
DIMENSIONS	440 x 232 X 125 mm deep
WEIGHT	4.3 kg
ACCESSORIES	Wall mount bracket Interconnect cable, BNC



+ Info:
<https://fonestar.com/IR-600T>