

SYSTEMS AND CONTROL / ZONE SYSTEMS / DIGITAL

## **TAB-10-16**

10" ANDROID TOUCH SCREEN TO RUN THE NMX SERIES MATRIX USER INTERFACE APP.



























Programmable and customisable with PC control software.



Simple connection via RJ45 Ethernet and POE power.



VESA 75 x 75

+ Info:

https://fonestar.com/TAB-10-16



## ESPECIALLY RECOMMENDED IN:







Sports facilities

Hotels

All sectors

## **DESCRIPTION**

10" Android touch screen. Touch screen based on an Android tablet to run the user interface App of the NMX series matrices. It provides a customised user interface with the most common functions. It simplifies system management for the end user, interacting locally without the need to access the complex matrix configuration. Programming of the user interface is done with the PC control software. You can select functions such as volume control, gain control, mute, scene recall and special actions with UDP, RS-232 or RS-485 commands. The user interface App, available for Android and iOS, is required. The touchscreen has Ethernet connection with RJ45 for a stable connection, and POE power supply. Touch screen with user interface for applications where volume control and source selection is required locally in the zones, as well as other actions. Such as music bars, restaurants, hotels, shopping centres, conference rooms, etc.

## **TECHNICAL CHARACTERISTICS**

FEATURES	10" touch screen based on Android 2G + 16G tablet.  To run the NMX Series Matrix User Interface App.  Programmable and customisable with PC control software.  The main functions are volume control, gain control, Mute, scene call and UDP, RS-232 or RS-485 commands.  Supports multiple touch screens in one installation.  Connection via RJ45 Ethernet and POE power supply.  Compatible with VESA 75 x 75 mount.
INPUTS	1 x LAN port for local area network connection, RJ-45 2 x USB ports 1 x SD port 1 x USB serial port 1 x Micro USB OTG
OUTPUTS	1 x 3.5 mm Headphones
CONTROLS	Power, home, brightness and volume buttons
POWER SUPPLY	POE and 12 V DC, 1.5 A
DIMENSIONS	255 x 170 x 30 mm depth Compatible with VESA 75 x 75 mounts
WEIGHT	0.8 kg
ACCESSORIES	Wall installation mount



+ Info:

https://fonestar.com/TAB-10-16

**FONESTAR** 

Poligono Trascueto. 39600 Revilla de Camargo. Cantabria (España)





